




# PMC-1553

## Multi-Channel 1553 Interface for PMC Carriers/SBCs



Cable Assemblies  
Optional (DB 50 for  
I/O Shown)

Alta Data Technologies' PMC-1553 interface modules (PCI Mezzanine Card for Carriers and Single Board Computers) are multi-channel (1-4) 1553 cards supported by the latest software technologies. These PMC cards are based on the industry's most advanced 32-bit 1553 FPGA protocol engine, **AltaCore™**, and by a feature-rich application programming interface, **AltaAPI™**, which is a multi-layer ANSI C, C++, Windows .NET, Linux and most RTOSes. This hardware and software package provides increased system performance and reduces integration time.

**AltaCore-1553** is guaranteed 1553A/B/C Notice II & IV compliant and all cards are manufactured to the highest IPC-Level 3 standards and ISO processes. Cards are available in dual-function (BC/Mon or multi-RT/Monitor) or full-function (BC, mRT and Mon) configurations. Playback and Signal Generation are part of BC operations. Alta is committed to a risk-free integration and will be glad to help with any level of your system development.

AltaView & AltaRTVal  
Multi-Protocol Analyzer & 1553 AS4111/4112 5.2 Validation  
User's Application with Modular, Portable **AltaAPI**

### AltaAPI Architecture

**Layer 2** – Windows Managed DLL  
Object Oriented Code for .NET, C#, C++, VB, LabVIEW  
Network Client/Server C#

**Layer 1** – Portable ANSI C Application Program Interface (API)  
(most applications tie-in here – includes native LabVIEW/LabWindows CVI DLL)

**Layer 0** – OS Device Driver  
Windows, Linux, Real-Time Operating Systems, LabVIEW-RT

Hardware – PCI, PCI Express, cPCI, PCCD, XMC, etc...

Alta's Advanced Software Architecture

### Key Features:

- One to Four Independent, Dual Redundant MIL-STD-1553 Channels
- Dual Function (BC/Mon or mRT/Mon) or Full Function (BC/mRT/Mon)
- One Mbyte of Memory per Channel
- Fully Compliant to MIL-STD-1553A/B/C Notice II/IV, MIL-STD-1760 and Link-16
- **One of the Most Popular 1553 Cards in the Market with 1000s Deployed**
- Commercial or Industrial Extended Temperature Parts, Conduction Cooled and Rear Panel Optional
- Advanced 32-bit BC, RT and Monitor FPGA Design – Full 32 bit Memory.
- BC Framing/Subframing/Aperiodic
- Common Data Packets (CDP) for BC, RT and Monitor – Complete Message Info
- Advanced, Multi-layer **AltaAPI** Provided at No Cost with Source Code
- Windows, Linux, RTOS, LabVIEW & RT
  - .NET Managed DLLs
  - Contact Factory for Latest RTOS Support
- True HW Playback – HW Sync Channels
- Industry First: 20ns Signal Generation
  - Bit Construction – 1553 PHY TX
  - Supports RT Validation Testing
- IRIG-B RX PAM or RX/TX PPS Ext Clock
- Avionics Level & RS-485 Discretes/Clk
  - 1760 Ext RT Addressing
- Advanced BIT Features and Dual Temperature Sensors
- Full HW Interrupt Features
- PCI 32 Bit, 33/66MHz & PCI-X Compatible

# Multi-Channel (1-4) PMC-1553 Specifications

## General

- 32-Bit PCI 33/66MHz/PCI-X Compatible
  - PCI-SIG PCI 2.1 Compliant
  - ANSI/VITA 20-2001 Compliant
- One Megabyte RAM per Channel
- Common Data Packets (CDPs) for all BC, RT and Monitor Functions – Industry First
- MIL-STD-1553A/B/C Notice II & IV
  - MIL-STD-1760,1553A and Link-16
- Weight: 4oz/120grams
- Power (Estimated @ Max Bandwidth)
  - 1CH@5.5W, 2CH@6.5W, 3CH@7.5W, 4CH@8.5W
- Parts Temp (C) : -55 to +120 Storage, 0 to +70 Commercial, -40 to +85 Extended
- SCSI 3 Cable Assembly with 1553 3-Plug Stub Cables Provided. DB50 Optional for Trig/Clk/IO.
- 14 Avionics and Two RS-485 Discretes
- 1 Channel 1760 Ext RT Address Power-Up
- Loop-Back & User BIT, Dual Temp Sensors
- IRIG-B RX PAM and TX/RX PPS Time Sync
- IPC Class 3 and ISO 9001:2008 Processes

## BC Features

- Simple One-Shot Lists to Advanced Message Framing and Subframing
- Message Timing with 100 nSec Accuracy
- Infinite Linked CDP Data Buffers
  - 64-Bit, 20 ns Time Tags, Interrupts, Triggers
- Low and High Priority Aperiodic Messages
- Multi Branching Per Message, No-Ops, Delays, Ext Trigger In/Out, Interrupts etc...
- Up to 15 Retries Per Message
- Legal and Reserved Mode Codes
- 1553A and 1553B Support
- Full Error Injection/Detection

## Playback/Signal Vector PHY TX

- Real Hardware Playback from Archive Files
- Multi Channel and Multi Card Playback Clock Synchronization - 100 nSec Accuracy
- Signal Vector Generation at 20 nsecs \*\*INDUSTRY FIRST\*\*
  - Construct 1553 Bit Signals at 20 nsecs
  - \*\*AS4111 5.2 RT Val Protocol Capability
  - Advanced BC, RT or any 1553 PHY Signal TX

## RT Features

- Infinite Linked CDP Data Buffers
  - 64-Bit, 20 ns Time Tags, Interrupts, Triggers
- Legal and Reserved Mode Codes
  - 1553A and 1553B Support
  - Full Buffering of All Mode Codes
- Full Error Injection/Detection

## Monitor

- Sequential and RT Mapped Monitoring with Infinite Linked CDP Data Buffers
  - Available with All Card Models
  - 64-Bit, 20 ns Time Tags, Interrupts, Triggers
  - Full Error Detection

## Software: *AltaAPI*, *AltaView*, *AltaRTVal*

- Multi-Layer *AltaAPI* Architecture to Support Windows and ANSI C Linux, VxWorks, Integrity, etc...
  - Contact Factory For RTOS Platforms
  - LabVIEW & RT Support
- Optional *AltaView* is Based on the Latest Windows MS Office User Interface Style with Ribbon-Bar
  - Full Analyzer Integration Tool
- Optional *AltaRTVal* provides full AS4111/4112 5.2 RT Validation GUI and Reports

## Part Numbers

Dual Function Models: BC/Mon or mRT/Mon

- **PMC-1553-1D/2D/3D/4D-T**

Full Function Models: BC, mRT and Monitor

- **PMC-1553-1F/2F/3F/4F-T**

**Options:** -E for Ext Temp Parts (-40 to +85C), -C for Ext Temp, Conduction Cooled/Conformal Coated/Rear Panel, -R for Rear Panel P4 Commercial, -A for AltaView and -B for AltaRTVal. Ask factory about cable options.

## 5 Year Limited Warranty!

EU and China RoHS Compliant

Contact Alta for Special Lead Build Configurations

*AltaAPI* Software with ANSI C Source, .Net Managed DLLs and LabVIEW & LabVIEW-RT Provided at No Cost.

**Alta Data Technologies LLC**  
**4901 Rockaway Blvd., Building A**  
**Rio Rancho, NM 87124 USA**  
**888-429-1553 (in US)**  
**505-994-3111 (outside US)**  
**alta.sales@altadt.com**  
**www.altadt.com**